

SUNFIRE-REMOTE 400



PRODUCT

Sunfire-Remote 400 provides off-grid power to stationary or semi-mobile applications. An integrated IP interface for telemonitoring and long maintenance intervals enable unattended operation for more than a year. This makes Sunfire-Remote 400 ideal for use in secluded areas. Reliably, the compact unit operates at a temperature range from -20 to +55 °C / -4 to 131 °F (-40 °C / -40 °F optionally).

APPLICATIONS

- + **Oil & Gas:** SCADA and communication systems, cathodic corrosion protection, remote-controlled gate valves at pipelines, etc.
- + **Security & Safety:** Video surveillance systems, access control, traffic control, etc.
- + **Telecommunications:** microwave radio repeater stations, private LTE / 5G tower, back-up power in extreme weather areas, etc.
- + **Further Applications:** Environmental monitoring, meteorology technology, drones, etc.

SELECTED PROJECTS

- + **Germany, Deutsche Bahn AG:** In various locations, Sunfire-Remote 400 powers traffic lights and barriers at level crossings during wintertime.
- + **USA, leading telecom network operator:** Combined with photovoltaic systems, Sunfire-Remote 400 ensures the operation of several microwave radio stations in Alaska.
- + **Tibet, Furtenbach Adventures GmbH:** For an whole season, Sunfire-Remote 400 provided energy at the base camp on Mount Everest. For this purpose, two units were adapted to the high altitude.

CORE ADVANTAGES

- + **Autonomous**
Low maintenance enables unattended operation > 1 year
- + **Durable**
3x longer product life cycle than comparable off-grid fuel cell generators
- + **Robust**
Reliable primary power supply even under harsh conditions
- + **Easy**
Simple installation and operation
- + **Clean**
Environmentally friendly thanks to low emissions and low noise



SUNFIRE-REMOTE 400 – TECHNICAL DATA



SUNFIRE-REMOTE 400	
Fuel	Propane / Natural Gas
Electrical power	60 ... 350 W
Max. daily electrical output	8,4 kWh/day
Rated voltage	Battery voltage between 21 V = undervoltage limit ... 27.5 V shutdown
Thermal output	None
Fuel consumption	Propane: 75 ... 106 g/h / (0.17 ... 0.23 lbs/h) Natural gas: 0.094 ... 0.136 Nm ³ /h / (3.32 ... 4.80 standard ft ³ /h)
Gas connection	8 mm / 0.039 inches compression fitting
Pressure of gas connection	18 ... 50 mbar / 0.26 ... 0.73 psi
Weight	65 kg / 144 lbs
Dimensions	660 × 540 × 400 mm / 26.0 × 21.3 × 15.7 inches
Ambient temperature for operation	-20 ... +55 °C / -4 ... +131 °F (-40 °C / -40 °F optionally)
Water / lubricant consumption	None
Noise emission	<55 db(A) optionally with silencer
IP protection category	IP50
Communication	Ethernet TCP / IP
Essential accessories for operation	Battery VRLA 24 V, > 300 Ah, low pressure regulator, gas line and gas hose,
Other products / applications	SF-PB: As a hybrid system (photovoltaic) - 1.2 kW peak power 230 V AC with the Sunfire-Remote Powerbox 1200 compact solution or the Sunfire-Remote Powertrailer 1200 mobile solution
	SF-PC: Powering existing systems - e.g.: SCADA with 600 W DC peak power with the compact solution Sunfire-Remote Cabinet 600
Certification	CE; ANSI/CSA FC1 certification for North America